

HOLDER

9700 with Primaro Timber Trailer

MERIDIAN TRACTOR INC.

P.O. BOX 610-330 N. GLENWOOD

JACKSON WYOMING 83001

1-877-733-3882

WWW.HOLDERTRACTOR.COM



Timber Trailer

The Primero forwarder trailer is a useful addition to the active woodlot owner's arsenal of logging machinery. It is a true forestry trailer with a square central frame. The stake frames can be moved up and down the central frame to meet the needs of the user. The bogie axle can also be moved to a preferred location on the frame. Three stake pairs are standard on the trailer, extra stake pairs can be added if needed. Another useful feature is the hydraulic steering from the trailer tongue. This feature enables sideshift of the trailer "on the run". The operator can make the trailer follow in the same tracks as the tractor, reducing the need for wide trails and reducing damage to the residual stand. The side-shift also extends the reach of the loader because the sideshift can be used to move the loader out for more reach. The trailer has a flotation bogie with 14 ply rating floatation forest tires. The large 15 3/4" wide tires keep compaction of the ground and damage to the roots of the residual stand to a minimum. The loader has several features usually found only in loaders built for professional use. The powerful four cylinder rack and pinion turning mechanism provides 6490 foot pounds of torque. Loading in uneven ground is therefore not a problem for the Primero. The hydraulic outrigger legs contribute to good balance also in uneven terrain. The loader has a full 360 degrees of rotation. The life of the hydraulic hoses is extended by the spiral hose protections. The base machine includes the following features: Outrigger legs, two lever joystick valve, head-board screen, three stake frames, hydraulic steering tongue, bypass grapple.

Technical Data: Trailer

Load capacity	17,600 lb.
Load volume	2.74 cu yards
Central frame dimensions:	5 1/2" x 5 1/2 x 25/64
Ground clearance	20 7/8"
Hydraulic steering	included
Hydraulic outriggers	included
Stake frames	3 included
Tires	400/60-15.5-14ply r.
Length	18' 4 1/2"
Width	6' 10 5/8"
Weight, loader and trailer combo	3960 lb.

Technical Data: Loader

	<u>3351</u>	<u>3360</u>
Loader		
Reach	16' 8"	19' 8"
Max lifting torque	33kNm	33kNm
Max lifting capacity at	16' 8" reach 880lb.	660 lb.
Rotation torque kNm/ft-lb.	8.8/6490	8.8/6490
Rotator cylinders	4	4
Rack and pinion rods	2	2